

# Flooring Oddz and Endz

## Thechnical Data Sheet

Item	EN Norms	Result	ASTM Norms	Result	Remark
Size	EN 427	1219.2x228.6x3mm	ASTM F536	1219.2x228.6x3mm	
Dimension Squareness and Straightness	EN 427	Squareness:0.18mm			
		Straightness:0.07mm			
Chemical Resistance	EN 423	Pass	ASTM F925	Pass	available upon request
Color Fastness to Artificial light	EN 20105:B02 method A	Pass, >=Grade6	ASTM F1515	Pass	available upon request
Wear Resistance	EN 660-1	Weargroup: T			available upon request
Scratch resistance	ISO 10582	3500g	ASTM F3261	pass	available upon request
Resistant to impact			ASTM F1265	Pass	available upon request
Dimensional Stability	E434	Stability:Pass 0.1% Curling: 0.06mm	ASTM F1700	Pass,	
Residual Indentation	EN 433	Pass, 0.06mm	ASTM F970	Pass	
Slip Resistance	EN 13893	Class DS			
Behaviour to Fire	EN 13501-1	Bf1-S1	ASTM E648-06	Pass/Class 1	
Smoke Density			ASTM E662	Pass, <=450	

### Specifications

Length x Width(mm)	1219.2x228.6	overall thickness(mm)	3mm	Wearlayer(mm)	0.5
Gloss level	10+/-2	Virgin materials	Yes	bevel edges on 4 sides	No
UV matt coating	Yes	Floating installation	Yes	Click system	Micro bevel
Pieces/Carton	12	Square Meter/ Carton	3.345	Weight kgs/ Piece	1.67KGS
Cartons/pallet	60	Square Meter./ Pallet	200.67	Weight kgs/ Carton	22.2
Pallets /20'GP	20	Square Meter/ Container	4013	Weight kgs/ pallet	1332
Cartons deminsion (mm)	1250x232x50			Weight kgs/ 20'GP	26640